


TECHNICAL DATASHEET

Connection Box P130

A connection box which facilitates performance monitoring measurements of CPT corrosion protection systems

Monitoring

The surface mounted connection box facilitates performance monitoring measurements of CPT corrosion protection systems. This includes:

- System driving voltage
- Anode current
- Reinforcing steel potential (provided reference cell is used)

The measurements can be taken with a hand held digital voltmeter.

Future Treatment

Following initial treatment the terminals inside the connection box allow the measurement of currents and potentials and allow the option to re-apply DC voltage at any future time.

Dimensions

Connection blocks inside the box fit onto a standard DIN rail which allows customisation to suit specific site requirements.

Length	Width	Depth
130mm (5 1/8")	130mm (5 1/8")	75mm (3")

Other sizes are available

Material

1. Polycarbonate
2. RAL 7035 – Light grey
3. Temperature resistant up to 80°C

Ratings

1. Ingress protection: IP66/67
2. Impact resistance: IK08
3. Electrical insulation: totally insulated
4. Halogen free: 1
5. UV resistance: UL 508
6. Flammability rating: UL 746C 5"
7. Glow Wire Test °C: 960

Technical and Sales Support

w: www.cp-tech.co.uk

t: +44 (0) 115 9724 238

e: general@cp-tech.co.uk




For technical and sales support please contact us at:
Concrete Preservation Technologies
 1 Palmer Business Court, Manor House Road, Nottingham, UK, NG10 1LZ
 (T) +44 (0) 115 9724 238 (E) general@cp-tech.co.uk
www.cp-tech.co.uk